

Section V — HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE See II (Not Established for Product)

EFFECTS OF OVEREXPOSURE Inhalation: Anesthetic. Irritation of the respiratory tract
r acute nervous system depression characterized by headache, dizziness,
staggering gait, confusion, unconsciousness or coma. Others as noted in Sec. IX.

Skin or Eye Contact: Primary Irritation. Observe Sec. IX.

EMERGENCY AND FIRST AID PROCEDURES Inhalation: Remove from exposure. Restore breathing.
Keep warm and quiet. Notify a physician. Skin Contact: Wash affected
areas with water. Remove contaminated clothing. Consult a physician.
Eye Contact: Flush with water for 15 minutes. Consult a physician.

Section VI — REACTIVITY DATA

STABILITY ☐ UNSTABLE ☒ STABLE

CONDITIONS TO AVOID

INCOMPATIBILITY (Materials to avoid)

HAZARDOUS DECOMPOSITION PRODUCTS

Products of combustion are hazardous.

HAZARDOUS POLYMERIZATION ☐ MAY OCCUR ☒ WILL NOT OCCUR

CONDITIONS TO AVOID

Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Remove all sources of ignition. Avoid
breathing vapors. Ventilate area. Remove with inert absorbent and non-
sparking tools.

WASTE DISPOSAL METHOD Dispose in accordance with local, state and federal regulations.
incinerate in approved facility. Do not incinerate closed containers.

Section VIII — SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION In outdoor or open areas use NIOSH approved mechanical filter
respirator.

In restricted ventilation areas use NIOSH approved chemical-mechanical filters.

In confined areas use NIOSH approved air line type respirators or hoods.

VENTILATION Where employees may be exposed, provide general dilution or local
exhaust ventilation in volume and pattern to keep TLV of hazardous ingredients
in Section II below recommended (ACGIH) or regulated (OSHA) limit. Where
employees will not be exposed, keep LEL in Section II below 25% of limit.

PROTECTIVE GLOVES Recommended; ☒ Required

EYE PROTECTION Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT Prevent prolonged skin contact with contaminated clothing.

Section IX — SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Do not store above 120°F. Store large quantities
in buildings designed and protected for storage of flammable liquids.

OTHER PRECAUTIONS Do not take internally. Containers should be grounded when pour-
ing. Avoid free fall of liquid in excess of a few inches. Do not sand, flame
cut, braze or weld without NIOSH approved respirator or appropriate ventilation.
Observe container precautionary label warnings.

Inhalation of isocyanates can cause allergic sensitization. Symptoms may include
mucous membrane irritation, tightness of chest, irritation of respiratory tract,
coughing, headache, and shortness of breath. Asthma-like attacks may follow.
Observe Section VIII instructions.